



TUV T8

TUV T8 F17 1SL/25

TUV T8 lamps are double-ended UVC (germicidal) lamps used in professional water and air disinfection units. TUV T8 lamps offer almost constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Moreover, they have a long and reliable lifetime, which allows maintenance to be planned for in advance.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Main Application	Disinfection
Life to 10% Failures (Nom)	7500 h
Useful Life (Nom)	9000 h
System Description	-
Light Technical	
Color Designation	- [Not Specified]
Depreciation at Useful Lifetime	15 %
LLMF 6000 h Rated	12 %
Operating and Electrical	
Power (Rated) (Nom)	16.7 W
Lamp Current (Nom)	0.265 A
Voltage (Nom)	72 V


Approval and Application	
Mercury (Hg) Content (Nom)	2.0 mg
UV	
UV-C Radiation	4.5 W
Product Data	
Full product code	871150026413840
Order product name	TUV T8 F17 1SL/25
EAN/UPC - Product	8711500264138
Order code	927941904020
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927941904020
Net Weight (Piece)	100.000 g

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- DANGER: Risk Group 3 Ultra Violet product. These lamps emit high-power UV radiation that can cause severe injury to skin and eyes. Avoid eye and skin exposure to unshielded product. Use only in an enclosed environment which shields users from the radiation.

TUV T8



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TUV T8 F17 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604.0 mm

TUV TL-D 18W

Photometric data



TUV

TUV

